

# SCANNER DEORE Di2 - chameleon / hologram



**PRICE €3.088,55 | YEAR 2026 | FRAME 15,7"/S, 16,7"/M, 19"/L, 20,5"/XL**

|              |   |
|--------------|---|
| Colours      | chameleon / hologram  |
| Frame        | Carbon High Modulus 29"                                     |
| Fork         | RS SID SL Remote 100  |
| Chainring    | SHIMANO DEORE FC-M6100 12SPD 32T                            |
| Shifting     | SHIMANO DEORE SW-M6250 12SPD                                |
| Derailleur   | SHIMANO DEORE RD-M6250 12SPD                                |
| Freewheel    | SHIMANO DEORE CS-M6100 12SPD 10-51T                         |
| Chain        | SHIMANO M6100 12SPD   |
| Brakes       | SHIMANO DEORE BR-M6100 (180/160)                            |
| Brake levers | SHIMANO DEORE BL-M6100                                      |
| Front hub    | SHIMANO HB-TC500-15-B 15mm                                  |
| Rear hub     | SHIMANO FH-TC500-MS-B 12mm                                  |
| Rims         | MACH1 FZR-XC 29"  |
| Tires        | SCHWALBE Racing Ray 29x2,25 / SCHWALBE Racing Ralph 29x2,25 |
| Pedals       | ***   |
| Handlebars   | RITCHEY WCS 740mm   |
| Stem         | RITCHEY WCS   |
| Seatpost     | RITCHEY WCS CARBON  |
| Saddle       | SELLE ITALIA X3 BOOST                                       |

Bottom bracket  
Weight

Integrated Press Fit  
10.2

Recommended frame sizes are only approximate

| Frame size              | 15,7"/S | 16,7"/M | 19"/L | 20,5"/XL |
|-------------------------|---------|---------|-------|----------|
| Minimum height (cm)     | 155     | 165     | 175   | 185      |
| Maximum height (cm)     | 165     | 175     | 185   | 202      |
| Seat tube (mm) (A)      | 410     | 440     | 480   | 510      |
| Top tube (mm) (B)       | 582.9   | 607     | 630.2 | 654.3    |
| Chainstay (mm) (C)      | 425     | 425     | 425   | 425      |
| Wheelbase (mm) (D)      | 1100.6  | 1125.4  | 1150  | 1176.1   |
| Seat tube angle (°) (E) | 75      | 75      | 75    | 75       |
| Head tube angle (°) (F) | 68.5    | 68.5    | 68.5  | 68.5     |
| Reach (mm) (E)          | 422.5   | 445     | 465   | 485      |
| Stack (mm) (F)          | 598.7   | 604.7   | 616.4 | 631.7    |
| BB drop (mm)            | 64      | 64      | 64    | 64       |

